

# 2500 K

## Handling

Opening/closing 1 person app. 5 min.

### Weights

Gross vehicle weight max.

Tare weight basic type app.

Payload basic type app.

Payload stationary use

1.900 kg
1.070 kg
2.000 kg

#### **Dimensions**

#### Standard features

hot galvanized chassis with single axle, straight drawbar, EU standard overrunning and parking brake, 12 V EU standard lighting system, reinforced jockey wheel and support legs, complete bodywork with roof and open-up flaps made of insulated sandwich panels, full insulated cold store with entrance door at the front, 230 V 16 A 50 Hz reinforced cooling machine, storage compartment with access door for beverages or event furniture, cooled showcase with glass door for f.e. 115 x 33 cl bottles, rear draft counter with brushed NCS covering with sink, cold water tap and drip tray, 2 line draft beer system with additional dry cooler and wall mounted taps, LED spots in ceiling, 230 V 16 A basic electric system with German standard plugs, supply for fresh and used water with connections, PVC-corner covers, ...

## **Product advantages and features:**

- for all occasions, venues and events
- 12 months turnover and profit
- suitable for indoor use
- for professional serving and self-service
- compact draft beer and bottle solution
- "all-in" trailer with easy handling and logistic
- perfect for rental and self pick-up
- compact with low GVW and high payload
- transport with pre-chilled beverages and equipment
- setup time one person app. 5 minutes
- professional cooling and draft system
- eye-to-eye contact to the customer
- large covered sales area
- great optics and brand visibility
- cost saving shipping in high cube container

All weights and dimensions are app., in basic version as described above and according DIN 70020. We reserve the right for changes and modifications without prior notice. Pictures show special equipment. Errors and omissions reserved.









Type 2500 KF for bottles and cans









