

CBT 6000-2 AS

Handling

Opening/closing 1 person app. 10 min.

Weights

| 3.850 kg |
|----------|
| 3.500 kg |
| 350 kg |
| 2.300 kg |
| 1.550 kg |
| |

^{*} according directive 97/27/EG / downsizing to GVW 3.500 kg possible

Dimensions

| 8.180 x 2.550 x 3.0/0 mm |
|--------------------------|
| 5.890 x 2.340 mm |
| 2.370 mm |
| 6.060 x 3.880 mm |
| 5.100 x 1.400 mm |
| 2.310 x 2.280 mm |
| |

Standard features

Hot galvanized reinforced chassis, tandem axle with 14" tyres, hydraulic axle lowering system with 12 V power unit and cable remote control, energy set with battery, charger and manual emergency lifting, heigh adjustable drawbar with car coupler, EU standard overrunning and parking brake, 12 V EU standard lighting system, reinforced jockey wheel, reinforced crank supports in the corners, 20 ft. all-steel container body, front and side walls made of vertically beaded steel plates, wooden basic floor with plastic double floor with anti-slip surface, open-up sales flap with gas springs on the right side, double wing rear doors with exterior locking system, painting exterior/interior with open-up sales flat in 4-digit RAL colour (except metallic), 400 V 16 A basic electric system with German standard plugs, ...

Options

entrance door in front of fixed side wall, open-up sales flat on the left side, walk-in cold store, custom-made interior works, custommade longitudinal counters, draft beer and cooling systems, exclusive interior lighting, aluminum trussing, sound, TV and video systems, water supply, individual features, special painting, branding, changeable branding, roof displays, ...









PEKI GmbH

Am Neuhaus 2



All weights and dimensions are app., in basic version as described above and according DIN 70020. We reserve the right for changes and modifications without prior notice. Pictures show special equipment. Errors and omissions reserved. © PEKI 2023

