

# **CBT 6000-2 K/AS**

#### Handling

Opening/closing 1 person app. 10 min.

## Weights

Gross vehicle weight max.*	3.850 kg
Gross axle weight max.	3.500 kg
Gross nose weight (on coupler) max.	350 kg
Tare weight basic type app.	2.600 kg
Payload basic type app.	1.250 kg

\* according directive 97/27/EG / downsizing to GVW 3.500 kg possible

### **Dimensions**

Overall (without roof display) app.	8.180 x 2.550 x 3.070 mm
Rectangular sales area app.	4.570 x 2.340 mm
Interior standing height app.	2.370 mm
Cold store interior app.	1.250 x 2.250 x 2.250 mm
Open-up sales flap app.	4.100 x 1.400 mm
Covered sales area app.	6.060 x 3.880 mm
Rear frame inside app.	2.310 x 2.280 mm

#### Standard features

Hot galvanized reinforced chassis, tandem axle with 14" tyres, hydraulic axle lowering system with 12 V power unit and cable remote control, energy set with battery, charger and manual emergency lifting, heigh adjustable drawbar with car coupler, EU standard overrunning and parking brake, 12 V EU standard lighting system, reinforced jockey wheel, reinforced crank supports in the corners, 20 ft. all-steel container body, front and side walls made of vertically beaded steel plates, wooden basic floor with plastic double floor with anti-slip surface, full insulated cold store with aluminum floor and aluminum KEG protection coverage, entrance door at the front and passing door to the sales area, 230 V 16 A 50 Hz reinforced cooling machine, open-up sales flap with gas springs on the right side, double wing rear doors with exterior locking system, painting exterior/interior with open-up sales flat in 4-digit RAL colour (except metallic), 400 V 16 A basic electric system with German standard plugs, ...

## **Options**

entrance door in fixed side wall, open-up sales flat on the left side, custom-made interior works, custom-made longitudinal counters, draft beer and cooling systems, exclusive interior lighting, aluminum trussing, sound, TV and video systems, water supply, individual features, special painting, branding, changeable branding, roof displays, ...












All weights and dimensions are app., in basic version as described above and according DIN 70020. We reserve the right for changes and modifications without prior notice. Pictures show special equipment. Errors and omissions reserved. © PEKI 2023





Phone: +49-6500-9141-0 Fax: +49-6500-9141-83 e-mail: info@peki.com www.peki.com

