

- / container
- / rectangular 3 m
- / custom made interior works



GVC 3000



Bar and Event Container

GVC 3000

Transport and Handling

platform car trailer
platform truck, trailer or semi-trailer
max. 4 container on semi-trailer
loading/unloading with forklift or crane

Weights

Gross weight max. 5.000 kg
Tare weight basic type app. 1.000 kg

Dimensions

Overall (without roof display) app. 2.991 x 2.500 x 2.590 mm
Rectangular sales area app. 2.830 x 2.340 mm
Interior standing height app. 2.370 mm
Open-up sales flap(s) on side max. 2.300 x 1.250 mm
Open-up sales flap on front max. 1.750 x 1.250 mm
Rear frame inside app. 2.310 x 2.280 mm

Standard features

10' all-steel container, ISO corner castings, front and side walls made of vertically beaded steel plates, roof made of beaded steel plates, wooden basic floor with plastic double floor with anti-slip surface (food safe), open-up sales flaps optional on front/left/right with gas springs, double wing rear doors with exterior looking system, painting exterior/interior with open-up sales flap in 4-digit RAL colour (except metallic), 400 V 16 A basic electric system with German standard plugs, ...

Options

special frame for small hookloader, entrance door in fixed side wall, open-up sales flaps in special dimensions, foldable floor elements, custom made interior works, central, longitudinal or rear counters, draft beer and cooling systems, exclusive interior lighting, aluminum trussing, sound, TV and video systems, water supply, individual features, special painting, branding, changeable branding, roof displays, ...



Frame for hookloader



Type GVC 3000 HT with rear bar



Type GVC 3000 HT with rear bar

All weights and dimensions are app., in basic version as described above and according DIN 70020. We reserve the right for changes and modifications without prior notice. Pictures show special equipment. Errors and omissions reserved. © PEKI 2024



PEKI GmbH
Vehicles and Systems for Events
Am Neuhaus 2
DE-54317 Osburg / Trier Germany

Phone: +49-6500-9141-0
Fax: +49-6500-9141-83
e-mail: info@peki.com
www.peki.com

